

09/77/637
ASW
4-4-01

Applicant:

Müller Weingarten AG
Schussenstraße 11
88250 Weingarten

5

"Horizontal Transporting System"

Ans B1
10 Description

Ans B2
The invention relates to a press line or multi-stage press for large components, having a transporting apparatus for transporting workpieces, according to the preamble of Claim 1.

Ans B3
15 Prior Art

Ans B4
20 In a press, press line or multi-stage press for large components, transfer apparatuses are provided for transporting workpieces into the processing stages. Earlier transporting systems provided cam-drive-controlled longitudinal and lifting movements, and possibly transverse movements of the transporting apparatuses, which were derived from the
25 main drive of a press and were thus forcibly synchronized with the ram movement (EP 0 210 745, Figure 4). In recent systems according to EP 0 672 480 B1 or EP 0 693 334 A1, the transporting operation between individual processing stations takes
30 place individually by individual transporting apparatuses, which allow, in particular, a universal capacity for movement of the workpiece transportation between individual processing stages. By means of such a drive, which is fully independent of the central
35 drive of the press, or transportation of the workpiece with any desired degrees of freedom, it is possible to optimize the transporting operation of the workpiece in particular in relatively large press installations. For

By this purpose, you are referred to EP 0 672 480 or EP 0 693 334.

DE 4 309 661 A1 has disclosed a transporting apparatus
5 in which there are provided carrying rails which are
mounted in height-adjustable slides in the longitudinal
extent over the entire press length, above the
component-transporting plane. These carrying rails
serve for mounting purposes and as a track for
10 transporting carriages which each have dedicated drive
systems which are independent of one another. The
respective transporting carriages may be displaced
separately with a number of degrees of freedom. Mounts
for crossmembers are integrated in the transporting
15 carriages. The crossmembers are provided with retaining
elements, such as suckers, tongs or magnets, for
accommodating workpieces and transporting purposes. The
crossmembers are usually each retained and moved by two
lateral transporting carriages. The transporting system
20 disclosed is thus one in which transporting carriages
with a dedicated drive can be displaced independently
of one another on common horizontally arranged carrying
rails. The masses which are to be moved are relatively
large since, rather than being stationary, the drives
25 are displaced along as well.

DE 199 11 759, which was not published before the
priority date, discloses a transfer system for
component transportation comprising a number of
30 transporting systems which are arranged vertically on
the press uprights between the forming stages. Each of
these transporting systems has a dedicated drive
system.

35 It is proposed in the above document for two drives to
be configured, by regulation of rotational speeds and
direction of rotation in relation to one another, such
that a pivoting or transporting arm in operative
connection therewith can execute any desired traveling

curves in one plane. The disadvantage with the proposed system and the exemplary embodiments is the restriction to vertical attachment.

5 ~~Object and Advantage of the Invention~~

10 Taking the prior art as departure point, the object of the invention is to propose a highly flexible low-mass transporting system for forming machines which allows optimum adaptation of the movement sequences required by the component geometry and ensures this functionality in the case of horizontal attachment.

15 This object is achieved, taking a transporting system according to the preamble of Claim 1 as departure point, ~~by the~~ characterizing features of Claim 1. Advantageous and expedient developments of the transporting system are specified in the subclaims.

20 The invention is based on the idea of further developing the drive system described in DE 199 11 769 such that horizontal attachment is also made possible. This horizontal attachment is necessary, for example, when, on account of the geometry of the workpieces, the
25 transporting step is of such a magnitude that a vertical transporting system renders an increase in the press height necessary. A stationary attachment of 2 drives ensures the considerable reduction in the masses involved in the transportation. These drives can be
30 regulated independently of one another in terms of rotational speed and direction of rotation. In operative connection with movement-transmission means, the movements are combined and it is possible to execute any programmable traveling curve in one plane.

35

Pinions and racks may preferably be used as movement-transmission means.

Dm B5

09774637-043004

In contrast to a vertical attachment, the workpiece-bearing crossmember is fastened not on a pivoting lever but on an arm, slide or lifting column which executes a linear movement. The system comprises
5 transporting carriages which each have dedicated drive systems and guides. The number of transporting carriages depends on the number of forming stages of the press. In this case, it is also possible for the blank feeder which is necessary upstream of the first
10 forming stage likewise to be designed with this drive system.

In order to realize the independent routes of the individual transporting carriages, the drive systems
15 are offset in relation to one another transversely to the component-transporting direction.

Further possible movements can be achieved by using drives for achieving pivoting movements of the
20 crossmembers and thus for changing the position of the workpieces. For a sufficient clearance during die changeover, the entire transporting system, or the individual parts thereof, may be of height-displaceable design. The same apparatus may also be used to bring
25 the transfer system to an optimum height in relation to the respective die set.

A considerable advantage of the transporting system proposed is the straightforward adaptation to the
30 necessary transporting or step lengths even with a wide variety of different presses for large components. The adaptation to the required transporting step can take place just by a change in length of guide rails and movement-transmission means. By virtue of the design
35 outlay being reduced as well, this system is thus a cost-effective modular system. Each transporting unit can be operated in a temporally optimum fashion in dependence on the respective ram or interfering-edge position in order to achieve high cycle speeds with

short transporting times. It is likewise advantageous that each system can travel with dedicated step lengths and speeds, i.e. the acceleration values can be selected in dependence on the rigidity of the
5 respective workpiece.

The stationary attachment of the drive motors is also favorable; this reduction in the moving masses makes possible a very dynamic transporting system with low
10 power consumption. It is also favorable that the power supply is arranged in a stationary manner, which, by dispensing with moving lines, increases the function reliability.

Ans B17
15 Further advantages of the drive system are described in the inventor's DE 199 11 796, to which, in order to avoid repetition, you are expressly referred.

Additional details and advantages of the invention can
20 be gathered from the following description of a basic illustration and exemplary embodiments:

Ans B77
In the figures:

25 Figure 1 shows a view of part of a multi-stage press for large components with a horizontal transfer system,

Ans B87
30 Figure 2 shows a drive of the transfer system as a basic diagram with a table of movements,

Figure 3 shows a front view of the transfer system with 2 forming stages of the press,

35 Figure 4 shows a plan view of Figure 3,

Figure 5 shows a sectional illustration of a drive of the transfer system, and

Figure 6 shows a view of part of a multi-stage press for large components with a vertical transfer-system drive.

DMB 97 5 Description of an Exemplary Embodiment

Figure 1 illustrates processing or forming stages of a multi-stage press 1 for large components. The transfer system 2 according to the invention extends over the entire press length, as seen in the transporting direction. The drive and guides are installed in a horizontal arrangement with fastening points on press uprights 3. An adjusting apparatus 4 for the central or groupwise displacement of the transfer system 2 in the vertical direction is also located here. This function may be necessary for die changeover, for avoiding a collision between the die 5 and the transfer system 2. This is thus purely a set-up axis. A height adjustment of the transfer system 2 is possible as a further set-up function. Different transporting positions can be seen in the illustration. While, in the forming stage 6.1, workpiece removal by transfer system 2.1 is taking place, the transfer system 2.2 is in the parked position alongside the forming stage 6.2. The transfer system 2.3 is located in the forming stage 6.3 in the middle of a transporting function with the component mount pivoted. The different positions of the rams 7 can also clearly be seen, i.e., on account of the flexibility of the transfer systems 2.1 - 2.3, the press can be operated with phase-offset rams. The maximum loading to which the press is subjected by the deformation forces is thus considerably reduced, as is thus the torque on the drive shaft.

DMB 107 35 The schematic illustration in Figure 2 shows the drive concept of a transporting system. Drives A1, A2 set gearwheels 8, 9 in rotation or keep them in the rest position. These gearwheels 8, 9 act on racks 10, 11 and thus affect the horizontal position thereof. At the

B10

5 same time, the racks 10, 11 are in operative connection
with the gearwheel 12. Rack 13 is driven by a gearwheel
12 and executes a vertical movement. The actual mount
and retaining means for the workpiece transportation are
10 fastened at the point of articulation 14 of the rack
13, as will be described in more detail in the
following figures. In the arrangement proposed, it is
thus possible, by regulating the drives A1, A2, for the
point of articulation 14 to reach any desired point in
an X-Y co-ordinate system with its traveling curve.

15 Table 15 shows the possible movements with identical
rotational speeds for A1 and A2 and with one drive at a
standstill in each case. The illustration does not
contain the large number of variants which may also
additionally be achieved by different rotational speeds
for A1 and A2.

20 The arrows illustrated in the table under A1/A2 show
the direction of rotation of the drives in each case. X
and Y are the axes of a planar co-ordinate system and
the arrows indicate the movement direction in
dependence on A1 and A2. By combining the movements, it
is thus possible to advance up to any point of the
25 planar co-ordinate system.

Dr B12

30 By way of example, the table 15 shows, with identical
rotational speed and direction of rotation of the
drives A1/A2, a purely vertical (Y-) movement of the
point of articulation 14 and thus a lifting or lowering
movement of the transporting system. A combination of
movements takes place by way of different rotational
speeds [sic] of A1/A2, to the extreme case where one
drive does not execute any rotational movement, as can
35 be seen from the last 4 schematic illustrations.

Dr B13

Gearwheels and racks are illustrated by way of example
in Figure 2 as movement-transmission means, but the
task is also fulfilled by other drive components, such

B13 as separately driven toothed belts with toothed-belt pulleys.

Details of the transfer system are illustrated in
5 Figure 3. The stationary drives 16, 17 produce the
movement of transfer system 2.1. Drive 16 is connected
to gearwheel 18, which acts on the horizontally
moveable rack 19. Drive 17 brings about, via a
gearwheel 20, the horizontal movement of the rack 21.
10 The racks 19, 21 are in operative connection with
gearwheel 22, 23, which drives the rack 24. The
construction and functioning of the rack 24 are
comparable with a lifting column. The transfer system
is of comparable construction to a cross-slide in terms
15 of the movement plane, i.e. it is mounted such that it
can be moved in 2 planes. By virtue of this
construction, it is possible to realize the movement
sequences which are described in more detail in Figure
2. For accommodating the workpieces, use is made of the
20 crossmember 25, which is fitted transversely to the
transporting apparatus and is provided with
component-retaining means. For accommodating and
driving the crossmember 25 on both sides, it is also
possible for the transfer system 2.1 to be attached
25 mirror-invertedly on the opposite press side.

one B14
If a change in position is necessary for removing a
workpiece or setting it down, crossbar or crossmember
25 may be of pivotable design. Crossmember 25 can be
30 pivoted about the pivot axis 27 and by the angle 28 by
means of a drive 26. Without the [sic] an intermediate
set-down location or orientating station is necessary,
the transfer system proposed travels the entire route
from, for example, forming stage 6.1 to forming stage
35 6.2 and the workpiece can be positioned correctly in
the process.

The transfer system 2.2, the movement sequence of which
is fully independent of transfer system 2.1, is of the

same design. The same drive parts are designated with index 1. To aid clarity, an illustration of the dies and workpieces has been dispensed with. The central adjusting and lifting apparatus 4 is not illustrated either.

Figure 4 shows a plan view of Figure 3, in which rack 19 is not illustrated. As an essential design feature, it can be seen that the respective drive elements of the transfer systems 2.1 and 2.2 are offset spatially. This arrangement ensures a collision-free movement sequence. The gearwheel 20, which is connected to the drive 17, thus has a longer hub than the analogous gearwheel 20.1. The gearwheel 20 drives the rack 21, which thus drives gearwheel 22. The rotational movement of gearwheel 22 is transmitted to the rack 24, via the common shaft 38, by the gearwheel 23.

To aid understanding of the movement sequence, you are referred again to Figure 2. Also illustrated in Figure 4 are the vertical linear guide 29 and the coupling system 30 for the crossmember 25.

Figure 5 shows the adjusting and lifting apparatus 4 and a detail of the transporting system 2 in a sectional illustration. The adjusting and lifting apparatus 4 has the function, on the one hand, of regulating the transporting system 2 to an optimum transporting height in relation to the die and, on the other hand, of moving the transporting system 2 vertically upward in order to avoid interfering edges during die changeover. This function can be carried out optionally for the entire transporting system 2 or just for individual transporting systems 2.1 - 2.n.

35

An embodiment with the possibility of individual adjustment is shown by way of example. Drive 31 drives, by way of example, a spindle-nut system 32 and this results in a change in position of the construction

angle 33 in the vertical direction. The transporting system 2 is mounted on the angle 33 in a horizontal arrangement, and the linear guide 34 which is necessary for the overall height adjustment is fitted vertically.

- 5 In an embodiment with central adjustment, a universal-joint shaft, which is connected to the central drive, would be provided instead of drive 31.

Of the transporting system 2.2, the following are
10 illustrated:

drive 16.1 with gearwheel 18.1, which drives rack 19.1, which is guided in horizontal linear guides 35. The movement of the rack 19.1 drives gearwheel 22.1, which
15 is connected to gearwheel 23.1 by a common shaft 38. The rack driven by the gearwheel 23.1 is designated 24.1. The movement-executing slide 36 is mounted in a moveable manner in the horizontal linear guides 37 and the vertical linear guides 29. Fastened at the bottom
20 end of the slide 36 is drive 26, which can be pivoted about pivot axis 27 [lacuna] crossmember 25, as is described in Figure 3.

242 B167
25 It can be seen, in particular, in Figure 5 the [sic], despite the large number of degrees of freedom, a very good design solution for the exemplary embodiment has been found. Of particular note here is the compact and rigid design, which has additionally been achieved with low moving masses, as a result of which the power
30 consumption of the drives is also reduced.

A further illustration, according to Figure 6, shows an alternative embodiment of the transporting system 2.

35 The stationary drives 39, 40 are arranged on the press upright 3. Drive 39 drives rack 42 via gearwheel 41, and drive 40 drives rack 44 via gearwheel 43. Racks 42, 44 are in operative connection with gearwheel 45, which is connected to gearwheel 46 by a common shaft 47.

Gearwheel 46 drives rack 48, as a result of which the transporting system 2 is driven in a manner which has already been described in detail. A toothed belt 49 with deflecting rollers 50, as further drive means, is novel here. Said toothed belt 49 is firmly connected, on the one hand, to vertical slide 51 at the fastening point 52 and, on the other hand, to the horizontal slide 53 at fastening point 54. If, then, a horizontal movement of the basic carrier 55 is initiated via the drives 39, 40 and the following gear chain, then, on account of the fixed points 52, 54, the toothed belt 49 executes a type of rolling movement, as a result of which the horizontal slide 53 likewise executes via fixed point 54, the horizontal movement of the toothed belt 49. This combination of movements results in an approximately double speed of the horizontal slide 53 in relation to the basic carrier 55. Crossmember 25 with the component-retaining means is coupled to horizontal slide 53. The crossmember 25 thus travels from forming stage 6.1 to forming stage 6.2, in any desired curve in the plane, during component transportation. By way of example, component removal takes place in forming stage 6.1, while the component is set down in forming stage 6.2. During the forming operation, the horizontal slide 53, with crossmember 25, is located in the parked position in the region of the upright.

For reliable guidance and mounting, linear guides 56 are fastened on the horizontal slide 53 and guide rails 57 are fastened on the basic carrier 55.

In the same way, vertical slide 51 is also mounted in linear guide 58 and guide rails 59, which are fastened on the upright 3.

A possibility of pivoting by the pivoting angle 28 about the axis of rotation 27 may, as is described in Figure 3, likewise be provided.

5

Abstract

List of Designations:

	1	Multi-stage press for large components
	2	Transporting system
5	3	Press upright
	4	Adjusting and lifting apparatus
	5	Die
	6	Forming stage
	7	Ram
10	8	Gearwheel
	9	Gearwheel
	10	Rack
	11	Rack
	12	Gearwheel
15	13	Rack
	14	Point of articulation of workpiece-retaining means
	15	Table of movements
	16	Drive
	17	Drive
20	18	Gearwheel
	19	Rack
	20	Gearwheel
	21	Rack
	22	Gearwheel
25	23	Gearwheel
	24	Rack
	25	Crossmember
	26	Drive
	27	Pivot axis
30	28	Pivoting angle
	29	Linear guide (vertical)
	30	Coupling
	31	Drive
	32	Spindle system
35	33	Construction angle
	34	Linear guide (vertical)
	35	Linear guide (horizontal)
	36	Slide
	37	Linear guide (horizontal)

- 38 Shaft
- 39 Drive
- 40 Drive
- 41 Gearwheel
- 5 42 Rack
- 43 Gearwheel
- 44 Rack
- 45 Gearwheel
- 46 Gearwheel
- 10 47 Shaft
- 48 Rack
- 49 Toothed belt
- 50 Deflecting rollers
- 51 Vertical slide
- 15 52 Fixed point
- 53 Horizontal slide
- 54 Fixed point
- 54 [sic] Basic carrier
- 56 Linear guide
- 20 57 Guide rails
- 58 Linear guide
- 59 Guide rail

TOP SECRET